

Audrey II

A5-2-R

Touch POS Terminal



FEATURES

- FHD and PCAP Anti-glare Glass
- Front panel IP65, whole unit IP54 certified
- HDMI 1920 x 1080 @ 60Hz Support
- Type-C USB
- Android 13

Audrey II

Specifications



Item	A5-2-R
Size	15.6"
Aspect Ratio	16:9
Resolution	1920 x 1080
Brightness	250 nits
Touch	PCAP Touch
CPU	RK3399 Dual-core Cortex-A72 up to 1.8GHz Quad-core Cortex-A53 up to 1.4GHz
Memory	DDR4 4GB
Storage	64G
I/O Interface	2 x serial ports, RS-232 (RJ45), 0V/5V/12V selected in UI (COM1, COM2) options 1 x LAN(IEEE 802.3 10/100/1000 Mbps) 1 x RJ11 port support for 2 cash drawers with 24V / 12V jumper setting 1 x DC +12V out 4 x USB 3.0(OTGx1) + 2 x USB 2.0 1 x DC +12V input 1 x audio (1 x line-out) 1 x HDMI 1 x Type-C (data transfer only)
Speaker	1 x speaker (3W)
Peripheral Options	MSR, EMV reader, fingerprint reader, RFID/ NFC, USB 2nd display, HDMI 2nd display, 2D bar code scanner, camera, IO extension box (EX-100, EX-101, EX-300), cash drawer, PS-103 Cosmo printer stand (space-saving stand, compatible with RP-700 or Epson TM-T70 II)
Wireless Option	Wi-Fi 5 IEEE 802.11b/g/n, BT 5.0 (on board)
Display Support	2 independent displays (Main Display + HDMI)
Spill & Dust Resistant	Front panel IP65, whole unit IP54 certified(NY)
Operating System	Android 13
TPM & vPro	N/A
Power Adaptor	AC-In 100~240V / DC-Out 12V, 65W
Reliability	System operating temperature: 0~40°C / 32~104°F System humidity: 15% ~ 80% Storage temperature: -20~60°C / -4~140°F
Dimensions (Wx Hx D)	364 x 288 x 201 mm / 14.33 x 11.34 x 7.91 in
Weight	5.4 kg / 11.9 lb

*Specification is subject to change without prior notice

Contact Now

TAIWAN E-mail:sales@partner.com.tw
USA E-mail:sales@partnertechcorp.com
EUROPE E-mail:info@partner-tech.eu
UK E-mail:sales@partnertechuk.com
CHINA E-mail:sales@partnertech.com.cn

MIDDLE EAST E-mail:info@partnertechme.com
AUSTRALIA E-mail:sales@partner-tech.com.au
SOUTH EAST ASIA E-mail:ptse@partner.com.tw
JAPAN E-mail:sales-jp@partner.com.tw

