

Audrey II

A5 II Series

Touch POS Terminal



FEATURES

- High performance Intel® CPU with fanless design
- On-Cell, Optical Bonded Display
- FHD and anti-glare Glass, Ultra-Thin 7mm Bezel
- Front panel IP65
- High speed M.2 SSD
- Support for Wi-Fi 6E
- Type C USB
- TPM 2.0
- Windows 11 IOT Enterprise GAC



Audrey II

Specifications



Item	A5-2-T	A5-2-E
Size	15.6"	
Aspect Ratio	16:9	
Resolution	1920 x 1080	
Brightness (typical)	400 nits	
Touch	oTP (On-cell Touch Panel), Slim-Edge 7mm Bezel Design (w/Anti-Glare)	
CPU	Intel® Celeron® 6305 (Tiger Lake UP3)	Intel® Celeron® J6412 (Elkhart Lake)
	Intel® Core™ i3-1115G4 (Tiger Lake UP3)	
	Intel® Core™ i5-1145G7, Vpro (Tiger Lake UP3)	
	Intel® Core™ i7-1185G7, Vpro (Tiger Lake UP3)	
Memory	DDR4 4GB, 8GB, 16GB, 32GB	
Storage	M.2 PCIe SSD: 128G / 256G / 512G	
External I/O Interface	2 x Serial Ports, RS232 (RJ45), 0V/5V/12V selected in BIOS (COM1, COM2)	
	1 x Intel LAN (IEEE 802.3 10/100/1000 Mbps Ethernet, RJ45)	1 x LAN (IEEE 802.3 10/100/1000 Mbps Ethernet, RJ45)
	1 x RJ11 port with support for 2 cash drawers with 24V / 12V jumper setting	
	1 x DC+ out 12V	
	4 x USB 3.2 + 2 x USB 2.0	2 x USB 3.0 + 4 x USB 2.0
	1 x DC +12V input	
	1 x Audio (1 x line-out)	
	1 x HDMI	
	1 x Type C (Data Transfer+ Display)	1 x Type C (Data Transfer only)
	Speaker	1 x Speaker (3W)
Peripheral Options	MSR, IC Card Reader, Fingerprint, RFID, i-Button, VFD, USB 2nd Display, HDMI 2nd Display, SCN-300, Camera-300, EX-300	
Wireless (option)	Wi-Fi 6E Intel AX210 IEEE 802.11 a/b/g/n/acR2/axR2, BT5.2	
Display Support	3 Independent Displays (Main Display + HDMI + Type C)	2 Independent Displays (Main Display + HDMI)
	IP54 Certified	
Operation System	1. Windows 11 IoT Enterprise GAC (64bit)	
	2. Windows 10 IoT Enterprise LTSC 21H2 (64bit) and newer version	
	3. Ubuntu 22.04	
Software	1. Intel V-Pro (i5/i7 CPU only)	S/W TPM 2.0 (BIOS)
	2. S/W TPM 2.0 (BIOS)	
Power Supply	AC-In 100~240V / DC-Out 12V, 65W	
Reliability	System Operating Temperature: 0~40°C/ 32~104°F	
	System Humidity: 15% ~ 80%	
	Storage Temperature: -20~60°C/ -4~140°F	
Dimensions (Wx Hx D)	364 x 252 x 223 mm / 14.33 x 9.92 x 8.78 inch	
Weight	3.7 kgs / 8.16 lbs	

*Specification is subject to change without prior notice

Contact Now

TAIWAN E-mail:sales@partner.com.tw
USA E-mail:sales@partnertechcorp.com
EUROPE E-mail:info@partner-tech.eu
UK E-mail:sales@partnertechuk.com
CHINA E-mail:sales@partnertech.com.cn

MIDDLE EAST E-mail:info@partnertechme.com
AUSTRALIA E-mail:sales@partner-tech.com.au
SOUTH EAST ASIA E-mail:ptse@partner.com.tw
JAPAN E-mail:sales-jp@partner.com.tw

