

Customer Display

CD-101CF

Customer Display Alternative Choice



FEATURES

- High resolution 1920 x 1080
- LED backlight LCD
- USB interface for low power consumption

Customer Display

Specifications

Item	CD-101CF	
LCD Display	10.1" TFT panel	
Max. Resolution	1920 x 1080	
Brightness	1000 cd/m2 (Max.)	
Contrast Ratio	1000 (Typ)	
Display Color	16.2M	
Response Time	30ms	
LED Backlight Life	30,000 hours	
Viewing Angle	Left/Right	85° (Typ)
	Upper	85° (Typ)
	Lower	85° (Typ)
OSD (On Screen Display)	Power button, Up & Down for brightness	
Power adaptor	USB 5V	
Dimesion	252.97 (L) x 163.00 (W) x 25.00 (D) mm / 9.96 (L) x 6.41 (W) x 0.98 (D) inch	
Touch (optional)	10-point PCAP Touch (USB interface)	
VESA Mounting	75 x 75mm	
Colors	Black, Silver	
Operating Conditions	Temperature	-20°C ~ 70°C / -4°F ~ 158°F
	Humidity	10% ~ 90%
Storage Conditions	Temperature	-30°C ~ 80°C / -22°F ~ 176°F
	Humidity	10% ~ 90%
Certification	CE, FCC, BSMI	

*Specification is subject to change without prior notice

Contact Now

TAIWAN E-mail:sales@partner.com.tw
USA E-mail:sales@partnertechcorp.com
EUROPE E-mail:info@partner-tech.eu
UK E-mail:sales@partnertechuk.com
CHINA E-mail:sales@partnertech.com.cn

MIDDLE EAST
AUSTRALIA
SOUTH EAST ASIA
JAPAN

E-mail:info@partnertechme.com
E-mail:sales@partner-tech.com.au
E-mail:ptse@partner.com.tw
E-mail:sales-jp@partner.com.tw

