

Alfred

PS-137

Interactive Stand-Alone Kiosk



FEATURES

- Versatile self-service kiosk
- Sleek & space-saving stand-alone design
- 21.5" full HD touch display (300 nits)
- Built-in 3-inch printer
- Customizable with many peripheral options
- Latest, high-performance Intel or Rockchip CPU
- Available for Android, Linux, and Windows

Alfred

Specifications



Item	Alfred PS-137		
Size	21.5"		
Aspect Ratio	16:9		
Resolution	1920 x 1080		
Brightness	300 nits		
Touch	PCAP Touch		
CPU	Alder Lake Intel® Core™ i3-1215U Intel® Core™ i5-1245U, vPro Intel® Core™ i7-1265U, vPro	Elkhart Lake Intel® Celeron® J6412	Rockchip RK3399
Memory	DDR4 4GB, 8GB, 16GB, 32GB		LDDR4 4GB
Storage	M.2 PCIe SSD: 128GB / 256GB / 512GB /1TB		eMMC 32GB + 1x micro SD card slot
I/O Ports	3 x serial ports, RS-232 (RJ45), 0V/5V/12V selected in BIOS (COM1, COM2, COM3)		2 x serial ports, RS-232 (RJ45) 0V/5V/12V selected in setting (COM1, COM2)
	1 x Intel LAN (IEEE 802.3 10/100/1000 Mbps)		1 x LAN (IEEE 802.3 10/100/1000 Mbps)
	1 x RJ11 port support for two cash drawers with 24V/12V jumper setting		
	1 x DC +12V out		
	4 x USB 3.2 + 2 x USB 2.0	3 x USB 3.2 + 3 x USB 2.0	1 x USB 3.0 (OTG) + 5 x USB 2.0
	1 x DC +12V input		
	1 x audio (1 x line-out)		
	1 x HDMI		
	1 x Type-C (data transfer + display)		1 x micro SD card
Printer	3-inch thermal printer		
Speaker	1 x speaker (3W)		
Peripheral Options	2D barcode reader, MSR, payment terminal bracket, RFID/NFC reader, ADA keypad, LED status light (multi-color)		
Wireless Options	Wi-Fi 6E (Intel AX210), IEEE 802.11 a/b/g/n/acR2/ax (2.4 GHz, 5 GHz, 6 GHz) BT 5.3		IEEE 802.11a/b/g/n/ac (2.4 GHz, 5 GHz) BT 4.2 (supports BLE)
Operating System	Windows 11 IoT Enterprise LTSC 24H2 (64 bit) Windows 10 IoT Enterprise LTSC 21H2 (64bit) Linux Ubuntu 22.04		Android 12
TPM & vPro	Intel vPro (i5/i7 CPU only) S/W TPM 2.0 (BIOS)	S/W TPM 2.0 (BIOS)	N/A
Power Adaptor	AC-In 100~240V / DC-Out 12V, 120W	AC-In 100~240V / AC-Out 12V, 90W	AC-In 100~240V / DC-Out 12V, 90W
Spill & Dust Resistant	Front panel IP65, entire unit IP54 certified		
Reliability	System operating temperature: 0~40°C / 32~104°F System humidity: 15% ~ 80% Storage temperature: -20~60°C / -4~140°F		
Dimensions (W x Hx D)	Landscape: 524 x 1480 x 400 mm / 20.6 x 58.3 x 15.8 in Portrait: 350 x 1576 x 400 mm / 15.0 x 61.9 x 15.8 in		

*Specification is subject to change without prior notice

Contact US

Partner Tech USA Inc.
1255 N. Patt Street
Anaheim, CA 92801
Phone: 949-598-1888
sales@partnertechcorp.com

Partner Tech Mexico & Latin America
Blvd. Palmas Hills 1, Piso 8, Valle de las Palmas, Huixquilucan
Ciudad de México, 52764, Mexico
Phone: 949-598-1888
info@partnertechcorp.com

