

AD-215-H

Hotel Self-Service Kiosk



The AD-215-H is a robust self-service kiosk designed with maximum efficiency, longevity, flexibility, and scalability to meet self-checkout requirements for hotels.

Self-service not only eliminates long waiting lines but also makes the check-in/check-out more convenient and private. Besides taking away the queue, the AD-215-H also offers various payment options and ways to interact with your customers. With an integrated high-quality document scanner, the AD-215-H provides accurate ID document authentication to speed up the check-in process.

It is the most optimized kiosk solution that can be customized to best fit your needs with a wide range of optional accessories, including camera, LED indicator, EMV terminal, and flyer holder.

SPECIAL FEATURES

- 21.5", FHD PCAP
- High performance Intel CPU, fanless design
- High speed M.2 PCIe
- ID and passport scanner
- Room key dispenser

OPTIONS

- RFID reader
- Front camera
- NFC
- LED status bar
- Payment Terminal bracket

For an optimized workflow



Base Options

Classic Counter Top



Floor Stand



AD-215-H

Item	AD-215-H	
Display	21.5" Resolution 1920x1080 (300 nits)	
Touch	PCAP touch	
CPU	Intel® Core™ i3-7100U (KABYLAKE-U) Intel® Core™ i5-7300U (KABYLAKE-U)	Intel Celeron J3455 (Apollo Lake)
Memory	DDR4 4GB, 8GB, 16GB	DDR3L 4GB, 8GB
Storage	M.2 PCIe SSD: 128G / 256G	M.2 SATA SSD: 128G / 256G
External I/O Interface	2 x Serial ports, RS232 (RJ45), 0V/5V/12V selection by BIOS (COM1, COM2)	
	2 x serial ports , D9P (COM3 , COM4)	
	2 x LAN, (IEEE 802.3 10/100/1000 Mbps Ethernet, RJ45)	
	1 x RJ11 port supports 2 cash drawer with 24V / 12V by jumper setting	
	1 x DC+12V out	
	6 x USB 3.0 (USB3.0/2.0)	
	1 x DC +12V input	
	1 x Audio (1 x Line-out)	
	1 x HDMI	
	Speaker	1 x Speaker 3W
Printer	3" Thermal printer	
Bar Code Scanner	2D Bar Code Scanner	
OCR Scanner	OCR SecureScan Manager	
Card Issuing Machine	Card Issuing Machine	
Optional Peripheral	EMV Terminal Bracket	
	5M Camera	
	RFID Reader	
	Bill / Bill recycle : Bill Width Accepted : 62~74 mm	
	Drum : 600 notes	
	Coin : Coin Accepted Size, Diameter : 15~33 mm / Thickness : 1.0~3.5 mm	
	DM Shelf	
	Wheels kit : Four wheels & one handle	
WIFI/BT(option)	2.4GHz/5GHz (IEEE 802.11a/b/g/n/ac), BT 4.2 (supports BLE)	
Display Support	3 Independent Displays (Main Display + VGA + HDMI)	
Spill & Dust resistant	N/A	
Operation System	1. Windows 10 IoT Enterprise (64bit) 2. Linux (Ubuntu 18.04) 3. Debian 9.12 x64 (Kernel 4.9.x)	1. Windows 10 IoT Enterprise (64bit) 2. Linux (Ubuntu 18.04) 3. CentOS 7.8 x64 4. Debian 9.12 x64 (Kernel 4.9.x)
	SW	1. Intel V-Pro (i5 CPU only) 2. S/W TPM 2.0 (BIOS)
Adaptor/Power Supply	System : AC-In 100~240V / DC-Out 12V, 120W	
	Card issuing machine module : AC-In 100~240V / DC-Out 12V, 120W	
Reliability	System Operating Temperature: 41~104°F for SSD	
	System Humidity: 15% ~ 80%	
	Storage Temperature: -4~140°F	
Dimensions	Counter Top : 19.37 (W) x 37.99 (H) x 14.02 (D) in	
	Floor Stand : 19.57 (W) x 67.01 (H) x 17.97 (D) in	

*Specification is subject to change without prior notice



PARTNER TECH USA INC.
 15320 Barranca Parkway Suite 150
 Irvine, CA 92618
 Phone: 949-598-1888
 sales@partnertechcorp.com

