



CARE . TRUST . RESPONSIBILITY

# SP-5514A TOUCH POS SYSTEM

ADVANCED POS FUNCTIONALITY WITH STYLE



For businesses that need robust point of sale (POS) functionality but don't want to make compromises when it comes to the look and feel of their stores or restaurants, Partner Tech's attractive and stylish all-in-one SP-5514A Android POS is the answer.

The SP-5514A Android POS features a small footprint that can be used even where space is limited. The all-in-one offers options to add a full complement of peripherals including encryption-capable MSR, BIO Reader, and NFC/RFID reader, to keep counters uncluttered.

## SPECIAL FEATURES

- Android 7.1
- Bezel-free 14" screen with projected capacitive touch (multi-touch)
- Multiple I/O configurations available

## OPTIONAL

- Available in Classic Black, Black & Metallic Grey and Silver & White
- Supports optional guest facing display (2x 20 VFD, 10.1")
- Optional peripherals including encryption-capable MSR, BIO Reader, NFC/RFID reader and EMV reader

**SP-5514A**

SP-5514A		
<b>CPU</b>		Cortex Quad Core
<b>LCD</b>	<b>Size</b>	Bezel free 14" LED-LCD, resolution 1366 x 768
	<b>Touch</b>	Projected capacitive touch (Multi Touch)
<b>RAM / Storage</b>		Standard: 2G / 16G Option: 4G / 32G
<b>Connection</b>	<b>LAN</b>	11 x RJ-45 10/100 Ethernet
	<b>WIFI/BT</b>	Option: 802.11b/g/n 2.4G, BT 4.0
<b>I/O</b>	<b>COM Ports</b>	2 x COM ports (1* RJ48, 1* DB9)
	<b>USB Ports</b>	4 x USB 2.0 (USB 4 support OTG)
	<b>RJ45 LAN Port</b>	1 x RJ-45 LAN port
	<b>RJ11 Port</b>	1 x RJ11 port (+24V)
	<b>MicroSD slot</b>	1 x TF slot (up to 64GB)
	<b>Power-jack</b>	1 x DC +12V input power-jack
	<b>HDMI</b>	1 x HDMI port
<b>Speaker</b>		1 x 3W speaker (internal)
<b>Operation System</b>		Android 7.1
<b>Power Supply</b>		AC100~240V/DC+12V,5.417A 65W power adaptor
<b>Dimensions</b>		14.45" (W) x 9.92" (D) x 11.69" (H)
<b>Options</b>	<b>Customer Display</b>	2*20 VFD
	<b>2nd Display</b>	10.1" LCD
	<b>Magnetic reader</b>	Encryption capable 3 track Magnetic reader ISO 7811 specification
	<b>EMV reader</b>	ISO7816 class A, B, C card
	<b>Below support 1 out of 2</b>	
	<b>Bio reader</b>	Encrypted fingerprint data; Pixel resolution: 512 dpi
	<b>RFID reader</b>	13.56MHz, ISO 14443-A/15693/18092

\*Specification is subject to change without prior notice



**PARTNER TECH USA INC.**  
 15320 Barranca Parkway Suite 150  
 Irvine, CA 92618  
 Phone: 949-598-1888  
 sales@partnertechcorp.com

