

# SP-1060

**PARTNER**

SP-1060 Series

Touch POS Terminal



## FEATURES

- Durable robust structure
- All in one POS with PCAP 15.6" screen
- Latest high-performance Intel CPU with fanless design
- Front panel IP65, whole device IP54 certified
- High speed M.2 SSD
- Support Win IoT Enterprise and Linux



Partner Tech Corporation

partnertechcorp.com

# SP-1060

**PARTNER**

## Specifications



	SP-1060	SP-1060-AL
Size	15"	
Aspect Ratio	4:3	
Resolution	1024 x 768	
Brightness (typical)	350 nits	
Touch	PCAP Touch	
CPU	Intel® Celeron® G3900, H110 Chipset Intel® Core™ i3-6100, H110 Chipset Intel® Core™ i5-6500TE, Q170 Chipset Intel® Core™ i7-6700TE, Q170 Chipset	Intel® Celeron® G6900TE (Alder Lake-S), H610 Chipset Intel® Core™ i3-12100TE (Alder Lake-S), H610 Chipset Intel® Core™ i5-12500TE (Alder Lake-S), Q670 Chipset Intel® Core™ i7-12700TE (Alder Lake-S), Q670 Chipset Intel® Core™ i9-12900TE (Alder Lake-S), Q670 Chipset
Memory	DDR4 4GB, 8GB, 16GB, 32G	
Storage	1 x 2.5" SATA HDD or SSD(Optional) / 2nd 2.5" SATA SSD or SSD(Optional)	
External I/O Interface	2 x Serial ports, RS232 (DB9), 0V/5V/12V selected in BIOS (COM1, COM2) 2 x Serial ports, RS232 (RJ45), 0V/5V/12V selection by JP (COM3, COM4) 2 x LAN IEEE 802.3 10/100/1000 Gigabit Ethernet 1 x RJ11 port with support for 2 cash drawers with 24V / 12V jumper setting 1 x DC+12V out 4 x USB 3.0, 2 x USB 2.0 1 x DC +12V input 1 x Audio (1 x line-out) 1 x HDMI 1 x VGA	
Speaker	1 x Speaker (3W)	
Peripheral Options	MSR, IC Card Reader, Fingerprint, RFID, i-Button, VFD, USB 2nd Display, VGA/HDMI 2nd Display	
Wireless (option)	Wi-Fi 6E Intel AX210 IEEE 802.11 a/b/g/n/acR2/axR2, BT 5.2	
Display Support	3 Independent Displays (Main Display + HDMI + VGA)	
Spill & Dust Resistant	IP54 Certified	
Operation System	1. Windows 10 IoT Enterprise LTSC 21H2 (64bit) and newer version 2. Ubuntu 18.04	1. Windows 11 IoT Enterprise GAC (64bit) 2. Windows 10 IoT Enterprise LTSC 21H2 (64bit) and newer version 3. Ubuntu 22.04
Software	1. Intel V-Pro (i5/ i7 CPU) 2. S/W TPM 2.0 (BIOS) 3. RAID (Q170 Chipset only)	1. Intel V-Pro (i5/ i7/ i9 CPU) 2. S/W TPM 2.0 (BIOS) 3. RAID (Q670 Chipset only)
Power Supply	AC-In 100~240V / DC-Out 12V, 120W	
Reliability	System Operating Temperature: 0~40°C / 0~104°F System Humidity: 15% ~ 80% Storage Temperature: -20~60°C / -4~140°F	
Dimensions (Wx Hx D)	360 (W) x 335 (H) x 237 (D) mm / 14.33 x 13.19 x 9.3 inch	
Weight	7.7 Kg / 16.98 lbs	

\*Specification is subject to change without prior notice

## Contact Now

**TAIWAN** E-mail:sales@partner.com.tw  
**USA** E-mail:sales@partnertechcorp.com  
**EUROPE** E-mail:info@partner-tech.eu  
**UK** E-mail:sales@partnertechuk.com  
**CHINA** E-mail:sales@partnertech.com.cn

**MIDDLE EAST** E-mail:info@partnertechme.com  
**AUSTRALIA** E-mail:sales@partner-tech.com.au  
**SOUTH EAST ASIA** E-mail:ptse@partner.com.tw  
**JAPAN** E-mail:sales-jp@partner.com.tw

