



» The Essential POS Enabler »

TEP-300

POS Thermal Receipt Printer

Main Features:

- Simple and elegant appearance with high optical mirror and easy paper loading.
- Low-noise thermal printing with auto cutter, full cut/partial cut optional
- 300mm/sec ultra high print speed, easy installation and maintenance.
- Includes a Paper Near End Detection Function (Beeper and Light Alarm)
- Desktop or Wall Mount (Optional)
- Supports high speed graphics and Supports Arabic Printing

Technical Specifications:

- Printing method: Direct Thermal Printing
- Printing Width: 72mm or 64mm
- Print Resolution: 203dpi
- Printing Speed: 300mm/s
- Paper Speed Width: 79.5 ±0.5mm
- Auto Cutter: 2.5 Million Cuts
- Interface : USB + Serial + Ethernet (Standard)
: Parallel + USB (Optional)
: USB + Serial + Ethernet + Bluetooth (Optional New)
: USB + Ethernet + Wi Fi (Optional New)
: USB + Serial + Wi Fi (Optional New)



Applications:

Supermarket	Warehouse	Merchant Establishment
Banks	Restaurants	Hotels
Malls	Hospitals / Pharmacy	School / Education Institution

Interface Type:

- 1 USB 2 ETHERNET 3 USB + Parallel 4 USB + SERIAL + ETHERNET (Standard)

Accessories:





TEP-300

POS Thermal Receipt Printer



Print:	Printing Method	Direct thermal printing
	Printing Speed	300mm/s
	Print Resolution	203dpi (8 dots/mm)
	Effective Printing Width	72mm & 64mm
	Printing Density	504 dots/line or 576 dots/line
	Character set	GB18030 (Simplified Chinese)
	Print font	ASCII Font A:12x24, ASCII Font B:9x24, Chinese: 24x24
	Character per line	Font A-42 lines or 48 lines/Font B-56 lines or 64 lines/Chinese-21 lines or 24 lines
Paper Spec:	Paper width	79.5±0.5mm
	Paper Roll Diameter	Ø80mm
	Paper Loading	Easy paper loading
Reliability:	MCBF	20 Million Lines
	Auto Cutter	1 Million Cuts
	Thermal printing head	100km
Barcodes:	UPC-A/UPC-E/EAN-13/EAN-	
Emulation:	ESC/POS/OPOS	
Driver:	WIN98/WIN2000/WINNT/WINXP/OPOS/WIN7/WIN8	
Paper out detection function:	Optional	
Power supply:	DC 24V,2.5A	
Cash drawer Control:	DC 24V,1A	
Interface:	USB + Serial + Ethernet (Standard)	
	Parallel + USB (Optional)	
	USB + Serial + Ethernet + Bluetooth (Optional New)	
	USB + Ethernet + Wi Fi (Optional New)	
	USB + Serial + Wi Fi (Optional New)	
Certificate:	FCC,CE,3C	
Physical:	Printer Dimension	195x145x148mm
Environment parameters:	Working temperature: 0~45°C; Storage: -10~50°C	
	Working humidity: 10-80%; Storage: 10-90%	



CARE . TRUST . RESPONSIBILITY



Download Our APP

Partner Tech Middle East Group

SALES OFFICE: Office No. 1004, 10th Floor, Aspect Tower, 33a, Al Mustaqbal Street, Business Bay, Dubai, UAE
 TECHNICAL & WAREHOUSE: Plot S10119, Gate 7, South Zone, Jebel Ali, Dubai, UAE
 SALES: +971 4 447 4273 | TECHNICAL & WAREHOUSE: +971 4 886 2980
 SALES: info@partnertechme.com | TECHNICAL SUPPORT: support@partnertechme.com

Distribution Brands

