



» The Essential POS Enabler »

# Xtreme II V2

## 15" POS Touch Terminal

- Brings Power into POS Design and Efficiency.
- Powerful Intel® Processor for your POS software and applications.
- Bezel free 15" TFT-LCD, LED backlight, Projected Capacitive Touch (Multi Touch).
- DDR3L memory supports up to 16GB
- Storage SSD (Default) / mSATA or HDD (Optional)
- Flexible modular design and optional customer display.
- Convenient compact POS and 45° tilt angle.



Printer Stand (optional)

### Customer Display:



1 2nd Display - VFD 2x20



2 2nd Display - 9.7" 1024 x 768



3 2nd Display - 15" 1024 x 768

### Interface:

- 1 \* VGA
- 3 \* USB 2.0, 2 \* USB 3.0
- 2 \* Serial (RS-232) Ports
- 1 \* RJ45 1000M LAN
- 1 \* Line out, 1 x Mic
- 1 \* 12V DC IN

SSD Mountable from the outside



### Applications:



Supermarket



Malls & Entertainment



Merchant Establishment



Hospitals / Pharmacy



Banks



Restaurants



Hotels



School / Education Institution



>> The Essential POS Enabler >>

# Xtreme II V2

## 15" POS Touch Terminal

### E-PoS XTREME Series

ITEM:	Xtreme II V2: E-POS-XIIV2-i5
CPU:	Intel® Core™ i5-4210U 1.70 GHz up to 2.70 GHz, 3M Cache
	Intel® Core™ i5-4250U 1.30 GHz up to 2.60 GHz, 3M Cache
	Intel® Core™ i5-4260U 1.40 GHz up to 2.70 GHz, 3M Cache
	Intel® Core™ i5-4300U, 3M Cache, 1.90 GHz up to 2.90 GHz
CPU: (Optional)	Intel® Core™ i5-6360U 2.00 GHz up to 3.10 GHz, 4M Cache
Memory:	4GB DDR3L 1333/1600MHz Optional up to 16GB, 2 x Slot (Standard 4 GB RAM)
Storage:	Storage SSD (Default) / mSATA or HDD (Optional)
Graphics:	Intel® HD Graphics
Display:	15" Active TFT color LCD, resolution 1024 x 768, brightness 350cd/m <sup>2</sup> , LED backlight
Viewing Angle:	45° adjustable
Touch Screen:	Capacitive Touch Panel
Audio:	ALC 662 6 channels, MIC and Line-out
LAN:	Realtek RTL8111H 1000M
Expansion Slot:	1 * Mini PCIE(WIFI, 4G module), 1 x EXP PCIE
Optional 2 <sup>nd</sup> Display:	9.7" 1024x768 / 15" 1024x768
External I/O Interface:	1 * VGA
	3 * USB 2.0, 2 * USB 3.0
	2 * Serial (RS-232) Ports
	1 * RJ45 1000M LAN
	1 * Line out, 1 x Mic
	1 * DC +12V input power-jack
Optional OS:	Windows 7 (32 & 64) Windows 10 and Windows 10 IoT LTSC, Linux
Optional Peripherals:	3-track MSR, VFD Display 2X20 characters(COM)
Input Power:	12V/2.5A power Adapter
Power Supply:	AC100~240V / 14 ~ 63Hz
Physical Dimensions:	354(L)*181(W)*341(H)cm
Operating Temp:	-10 ~ 60°C, 0-95% humidity



CARE . TRUST . RESPONSIBILITY



Download Our APP

### Partner Tech Middle East Group

SALES OFFICE: Office No. 1004, 10th Floor, Aspect Tower, Happiness Street, Business Bay, Dubai, UAE  
 TECHNICAL & WAREHOUSE: Plot S10119, Gate 7, South Zone, Jebel Ali, Dubai, UAE  
 SALES: +971 4 447 4273 | TECHNICAL & WAREHOUSE: +971 4 886 2980  
 SALES: info@partnertechme.com | TECHNICAL SUPPORT: support@partnertechme.com

### Distribution Brands

