

Audrey

A4 Series

Touch POS Terminal



FEATURES

- Sleek and modern design
- All in one POS with PCAP 15" screen
- Latest high-performance Intel CPU with fanless design
- Front panel IP65, whole device IP54 certified
- High speed M.2 SSD
- Supports Win IoT Enterprise and Linux

Audrey

Specifications



Item	A4-1-N	A4-1-AL	A4-1-E	A4-1-K
Size	15"			
Aspect Ratio	4:3			
Resolution	1024 x 768			
Brightness	400 nits			
Touch	PCAP Touch			
CPU	Alder Lake-N Intel® Processor N97 Intel® Core™ i3-N305	Alder Lake-P Intel® Core™ i3-1215U Intel® Core™ i5-1245U, vPro Intel® Core™ i7-1265U, vPro	Elkhart Lake Intel® Celeron® J6412	Kaby Lake-U Intel® Core™ i3-7100U Intel® Core™ i5-7300U
Memory	DDR4 4GB, 8GB, 16GB		DDR4 4GB, 8GB, 16GB, 32GB	
Storage	M.2 PCIe SSD: 128G / 256G / 512G / 1TB			M.2 PCIe SSD: 128G / 256G / 512G
I/O Interface	3 x serial ports, RS-232 (RJ45), 0V/5V/12V selected in BIOS (COM1, COM2, COM3)			2 x serial ports, RS-232 (RJ45), 0V/5V/12V selected in BIOS (COM1, COM2)
	1 x Intel LAN(IEEE 802.3 10/100/1000/2500 Mbps)	1 x Intel LAN(IEEE 802.3 10/100/1000 Mbps)	1 x LAN(IEEE 802.3 10/100/1000 Mbps)	2 x LAN(IEEE 802.3 10/100/1000 Mbps)
	1 x RJ11 port support for 2 cash drawers with 24V / 12V jumper setting			
	1 x DC +12V out			
	6 x USB 3.2	4 x USB 3.2 + 2 x USB 2.0	3 x USB 3.2 + 3 x USB 2.0	4 x USB 3.0
	1 x DC +12V input			
	1 x audio (1 x line-out)			
	1 x HDMI			
	1 x Type-C (data transfer + display + Power Delivery)	1 x Type-C (data transfer + display)		1 x VGA
Speaker	1 x speaker (3W)			
Peripheral Options	MSR, EMV reader, fingerprint reader, RFID/ NFC, i-Button, VFD, USB 2nd display, HDMI 2nd display, 2D bar code scanner, camera, IO extension box (EX-100, EX-101, EX-300), cash drawer, PS-103 Cosmo printer stand (space-saving stand, compatible with RP-700 or Epson TM-T70 II), LED indicator			
Wireless Option	Wi-Fi 6E Intel AX210 IEEE 802.11 a/b/g/n/acR2/axR2, BT 5.3			
Display Support	3 independent displays (Main Display + HDMI + Type-C)			3 independent displays (Main Display + HDMI + VGA)
Spill & Dust Resistant	Whole unit IP54 certified			
Operating System	1. Windows 11 IoT Enterprise LTSC 24H2 (64bit) 2. Linux Ubuntu 22.04	2. Windows 10 IoT Enterprise LTSC 21H2 (64bit) 3. Linux Ubuntu 22.04		1. Windows 10 IoT Enterprise LTSC 21H2 (64bit) 2. Linux Ubuntu 18.04
TPM & vPro	S/W TPM 2.0 (BIOS)	1. Intel vPro (i5/i7 CPU only) 2. S/W TPM 2.0 (BIOS)	S/W TPM 2.0 (BIOS)	1. Intel vPro (i5 CPU only) 2. S/W TPM 2.0 (BIOS)
Power Adaptor	AC-In 100~240V / DC-Out 12V, 65W / 90W			
Reliability	System operating temperature: 0~40°C / 32~104°F System humidity: 15% ~ 80% Storage temperature: -20~60°C / -4~140°F			
Dimensions (Wx Hx D)	360 (W) x 350 (H) x 201 (D) mm / 14.17 x 13.77 x 7.87 in			
Weight	6.2 kg / 13.67 lb			

*Specification is subject to change without prior notice

Contact Now

TAIWAN E-mail:sales@partner.com.tw
USA E-mail:sales@partnertechcorp.com
EUROPE E-mail:info@partner-tech.eu
UK E-mail:sales@partnertechuk.com
CHINA E-mail:sales@partnertech.com.cn

MIDDLE EAST E-mail:info@partnertechme.com
AUSTRALIA E-mail:sales@partner-tech.com.au
SOUTH EAST ASIA E-mail:ptse@partner.com.tw
JAPAN E-mail:sales-jp@partner.com.tw

