

Audrey

A7-1-Android

Touch POS Terminal



FEATURES

- Sleek & modern design
- Full HD 21.5" PCAP touch display
- High-performance ARM Rockchip CPU
- Front panel IP65, whole device IP54 certified
- High speed M.2 PCIe SSD
- Supports Android 11

Audrey

Specifications



Item	A7-1-Android
Display	21.5", 16:9, 1920 x 1080 (300 nits)
Touch	PCAP touch
CPU	Rockchip RK3399
Memory	LDDR4 4GB
Storage	eMMC 32GB + 1x Micro SD card slot (up to 128GB)
I/O Interface	2 x serial ports, RS-232 (RJ45), 0V/5V/12V selected in setting (COM1, COM2) 1 x LAN (IEEE 802.3 10/100/1000 Mbps) 1 x RJ11 port supports 2 cash drawer with 24V / 12V by jumper setting 1 x DC + 12V out put 1 x USB3.0 (OTG) + 5 x USB2.0 1 x DC + 12V input 1 x audio (1 x line-out) 1 x HDMI 1 x micro SD card
Speaker	1 x speaker (3W)
Peripheral Options	MSR, EMV reader, RFID/NFC reader, fingerprint reader, 5MP camera, 2D barcode scanner, thermal printer, I/O expansion box (EX-100, EX-101), printer stand, cash drawer, customer displays (VFD, 10.1", 11.6", 15.6")
Wi-Fi / BT (option)	2.4GHz/5GHz (IEEE 802.11a/b/g/n/ac), BT 4.2 (supports BLE)
Display Support	2 independent displays (main display + CD-101C or HDMI)
Spill & Dust Resistant	IP54 (whole unit), IP65 (front panel)
Operation System	Android 11
Power Adaptor	AC-In 100~240V / DC-Out 12V, 65W
Reliability	System operating temperature: 0~40°C / 32~104°F System humidity: 15% ~ 80% Storage temperature: -20~60°C / -4~140°F
Dimensions (Wx Hx D)	522 x 376 x 201 mm / 20.55 x 14.80 x 7.91 in
Weight	10 kg / 22.05 lb

*Specification is subject to change without prior notice

Contact Now

TAIWAN E-mail:sales@partner.com.tw
USA E-mail:sales@partnertechcorp.com
EUROPE E-mail:info@partner-tech.eu
UK E-mail:sales@partnertechuk.com
CHINA E-mail:sales@partnertech.com.cn

MIDDLE EAST E-mail:info@partnertechme.com
AUSTRALIA E-mail:sales@partner-tech.com.au
SOUTH EAST ASIA E-mail:ptse@partner.com.tw
JAPAN E-mail:sales-jp@partner.com.tw

