



CARE . TRUST . RESPONSIBILITY

SP-550 TOUCH POS SYSTEM

POWERFUL AND STYLISH



A modern and aesthetic POS system is critical to branding and overall customer experience provided at the checkout, but it must also have the power and functionality to allow you to serve customers efficiently. You can have it all with Partner Tech's SP-550 touch POS terminal.

Space-Saving Design

The Partner Tech SP-550 is a sleek, energy efficient POS terminal with a compact footprint. This allows retailers to optimize counter space and leaves room for sales boosters like impulse purchase displays. The SP-550 is an ideal solution for creating a lasting and positive final impression on the customer.

SPECIAL FEATURES

- Bezelfree 15" TFT LCD with LED backlight
- Projected Capacitive Touch (PCT)
- Supports up to 8GB RAM
- Wide range of interfaces, incl. USB 3.0
- 2nd monitor support
- Spill and dust resistant front panel, IP65

OPTIONAL

- Mini PCI-e, e.g. to support WiFi module
- Customer display (2x20 VFD or 7")
- 2nd monitor support (11.6" or 15")
- 3-track MSR
- RFID reader
- Bio reader
- IC card reader
- i-Button

SP-550

Item	SP-550									
CPU	Intel® Celeron™ J1900 (2.00GHz up to 2.42GHz), quad core, 2MB L2 Cache, fanless									
LCD	Bezelfree 15" TFT-LCD, resolution 1024 x 768, brightness 350cd/m², LED backlight									
Touch	Projected Capacitive Touch (Multi Touch) with USB interface									
RAM	DDR3L SO-DIMM, 2 slots up to 8GB									
Storage	1 x 2.5" SATA HDD or SSD (option) / 2nd SATA HDD or SSD (option)									
LAN	1 x RJ-45 10/100/1000 BASE-T Gigabit Ethernet									
I/O Interface	4 x COM (DC+0/5/12V: COM 1-2 BIOS selection, COM 3-4 by jumper) 5 x USB 2.0 1 x USB 3.0 1 x RJ-45 Ethernet 1 x RJ-11 Cash drawer control (for 2 cash drawers) 1 x VGA 1 x DC + 12V Out 1 x Mini PCI-e (internal) 1 x Audio connector (option)									
Speaker	1 x 3W speaker (internal)									
Operating System	Windows 7, POSReady 7, Windows 8.1, Windows 10, Linux (ubuntu)									
Power Supply	AC100~240V/DC+12V, 7.5A, 90W power adaptor									
Dimensions	360mm (W) x 237mm (D) x 335mm (H)									
Environment	<table border="0"> <tr> <td></td> <td>Operating:</td> <td>Storage:</td> </tr> <tr> <td>Temperature:</td> <td>0°C ~ +40°C</td> <td>-20°C ~ +60°C</td> </tr> <tr> <td>Humidity:</td> <td>15% ~ 80%</td> <td>15% ~ 80%</td> </tr> </table>		Operating:	Storage:	Temperature:	0°C ~ +40°C	-20°C ~ +60°C	Humidity:	15% ~ 80%	15% ~ 80%
	Operating:	Storage:								
Temperature:	0°C ~ +40°C	-20°C ~ +60°C								
Humidity:	15% ~ 80%	15% ~ 80%								
Options	3-track encryption-capable MSR, 2x20 line VF display Customer facing displays: 7", 11.6" or 15", Bio reader, IC card reader, i-Button, RFID/NFC									
Color	black (standard), black/white (option)									

*Specification is subject to change without prior notice



CARE . TRUST . RESPONSIBILITY

TAIWAN E-mail:sales@partner.com.tw
 USA E-mail:sales@partnertechcorp.com
 EUROPE E-mail:info@partner-tech.eu
 UK E-mail:sales@partnertechuk.com
 CHINA E-mail:sales@partnertech.com.cn

MIDDLE EAST E-mail:info@partnertechme.com
 AUSTRALIA E-mail:sales@partner-tech.com.au
 SOUTH EAST ASIA E-mail:ptse@partner.com.tw
 JAPAN E-mail:sales-jp@partner.com.tw